

Electric Dropbolts

Drop-bolt with Door Status Signal Output & Lock Status Indicator

Model EDB-D5C-TC

DESCRIPTION

Solenoid bolt is a flush mount type of electro-mechanical locking mechanism which is characterized by the use of a solenoid to throw the bolt. Designed for use in double acting doors and can be installed on inward-swinging or outward-swinging doors.



FEATURES & SPECIFICATION

- Fail Safe. Locked When Energized, with magnetic induction.
- Door Status Signal NC Output.
- Lock Status LED Indicator.
- Time Delay Feature - 0/3/6/9 seconds.
- Single Voltage - 12Vdc.
- Suitable for all kind of door with frame and 90/180 degree to open doors.
- Applicable for glass door with mounting brackets.

TIME DELAY SETTING

ON 1 2	0 SEC
ON 1 2	3 SEC
ON 1 2	6 SEC
ON 1 2	9 SEC

Models	EDB-D5C-TC
Lock Size	200 (L) x 35 (W) x 38 (H) mm
Strike Plate Size	100 (L) x 30 (W) x 12 (H) mm
Lock Tongue Size	Φ15 x 15 mm
Input Voltage	12VDC
Starting Current	650mA
Standby Current	250mA
Low Current Draw	4.5W
Working Temperature	-20 ~ 55°C